

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Revision date: 08/07/2014 Version

	Revision date: 08/07/2014 :	Version
SECTION 1: Identification of the su	ubstance/mixture and of the company/undertaking	
1.1. Product identifier		
Product form	: Mixture	
Trade name	: MASTER CARB & CHOKE CLEANER OTC COMPLIANT 16.25 OZ.	
Product code	: CB20CA	
1.2. Relevant identified uses of the su	bstance or mixture and uses advised against	
Use of the substance/mixture	: Carburetor Cleaner	
1.3. Details of the supplier of the safet	ty data sheet	
Master Chemical 4635 Willow Drive Medina, MN 55340 - USA T: 612-478-2360		
1.4. Emergency telephone number		
Emergency number	: CHEMTREC 24 Hour 1-800-424-9300	
SECTION 2: Hazards identification		
2.1. Classification of the substance or	r mixture	
Classification (GHS-US)		
Flam. Aerosol 2 H223 Compressed gas H280 Acute Tox. 3 (Oral) H301 Acute Tox. 3 (Dermal) H311 Skin Irrit. 2 H315 Repr. 2 H361 STOT SE 1 H370 STOT SE 3 H336 STOT RE 2 H373		
Full text of H-phrases: see section 16		
2.2. Label elements		
GHS-US labeling		
Hazard pictograms (GHS-US)		
Signal word (GHS-US)	GHS02 GHS04 GHS06 GHS07 GHS08 : Danger	

- : Danger
- H223 Flammable aerosol
- H280 Contains gas under pressure; may explode if heated
- H301+H311 Toxic if swallowed or in contact with skin
- H315 Causes skin irritation
- H336 May cause drowsiness or dizziness
- H361 Suspected of damaging fertility or the unborn child
- H370 Causes damage to organs
- H373 May cause damage to organs through prolonged or repeated exposure
- P201 Obtain special instructions
- P202 Do not handle until all safety precautions have been read and understood
- P210 Keep away from heat, sparks, open flames, hot surfaces. No smoking
- P211 Do not spray on an open flame or other ignition source
- P251 Pressurized container: Do not pierce or burn, even after use
- P260 Do not breathe dust,fumes,gas,mist,vapor spray
- P261 Avoid breathing dust,fume,gas,mist,vapor spray
- P264 Wash affected areas thoroughly after handling
- P270 Do not eat, drink or smoke when using this product
- P271 Use only outdoors or in a well-ventilated area
- P280 Wear protective gloves, protective clothing, eve protection, face protection
 - P301+P310 If swallowed: Immediately call a poison control center, doctor, physician,
 - P302+P352 If on skin: Wash with plenty of soap and water
- P304+P340 If inhaled: Remove person to fresh air and keep comfortable for breathing
 - P307+P311 If exposed: Call a poison center/doctor
 - P308+P313 If exposed or concerned: Get medical advice/attention

Precautionary statements (GHS-US)

Hazard statements (GHS-US)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

	 P312 - Call a POISON CONTROL CENTER, doctor, if you feel unwell. P314 - Get medical advice/attention if you feel unwell P321 - Specific treatment: See section 4.1 on this label P330 - Rinse mouth P332+P313 - If skin irritation occurs: Get medical advice/attention P361 - Take off immediately all contaminated clothing P362 - Take off contaminated clothing and wash before reuse P363 - Wash contaminated clothing before reuse P403+P233 - Store in a well-ventilated place. Keep container tightly closed P405 - Store locked up P410+P403 - Protect from sunlight. Store in a well-ventilated place P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F P501 - Dispose of contents/container to appropriate waste disposal facility, in accordance with local, regional, national, international regulations.
2.3. Other hazards	

Other hazards not contributing to the classification

: Contains gas under pressure; may explode if heated.

2.4. Unknown acute toxicity (GHS-US)

No data available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	Classification (GHS-US)
Acetone	(CAS No) 67-64-1	30 - 50	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
Toluene	(CAS No) 108-88-3	10 - 30	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304
Methanol	(CAS No) 67-56-1	10 - 30	Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation:dust,mist). H331 STOT SE 1, H370
carbon dioxide, liquefied, under pressure	(CAS No) 124-38-9	5 - 10	Compressed gas, H280

SECTION 4: First aid measures	
4.1. Description of first aid measures	
First-aid measures general	: Never give anything by mouth to an unconscious person. IF exposed or concerned: Get medic advice/attention. Call a POISON CENTER or doctor/physician.
First-aid measures after inhalation	: Cough. Remove to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER/doctor/physician if you feel unwell.
First-aid measures after skin contact	: Rinse skin with water/shower. Immediately call a POISON CENTER or doctor/physician. Remove/Take off immediately all contaminated clothing. Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation occurs: Get medical advice/attention
First-aid measures after eye contact	: Remove contact lenses, if present and easy to do. Continue rinsing. Rinse cautiously with wate for several minutes. Immediately call a POISON CENTER or doctor/physician. Obtain medical attention if pain, blinking or redness persist. Direct contact with the eyes is likely to be irritating
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention. Immediately call POISON CENTER or doctor/physician.
4.2. Most important symptoms and effe	cts, both acute and delayed
Symptoms/injuries	: May damage fertility or the unborn child. Suspected of damaging fertility or the unborn child. Causes damage to organs.
Symptoms/injuries after inhalation	: Shortness of breath. May cause drowsiness or dizziness.
Symptoms/injuries after skin contact	: Repeated exposure to this material can result in absorption through skin causing significant health hazard. Toxic in contact with skin. Causes skin irritation.
Symptoms/injuries after eye contact	: Causes serious eye damage.
Symptoms/injuries after ingestion	: Fatal if swallowed. Toxic if swallowed. Swallowing a small quantity of this material will result in serious health hazard.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 5: Firefighting measure	es a la companya de la
5.1. Extinguishing media	
Suitable extinguishing media	: Foam. Dry powder. Carbon dioxide. Water spray. Sand.
Unsuitable extinguishing media	: Do not use a heavy water stream.
5.2. Special hazards arising from the	e substance or mixture
Fire hazard	: Highly flammable liquid and vapor. Flammable aerosol.
Explosion hazard	: May form flammable/explosive vapor-air mixture. Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.
5.3. Advice for firefighters	
Firefighting instructions	: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment. DO NOT fight fire when fire reaches explosives. Evacuate area.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.
Other information	: Aerosol Level 2.
SECTION 6: Accidental release n	Deasures
	e equipment and emergency procedures
General measures	: No naked lights. No smoking. Isolate from fire, if possible, without unnecessary risk. Remove
General measures	ignition sources. Use special care to avoid static electric charges.
6.1.1. For non-emergency personnel	
Protective equipment	: Gloves. Safety glasses.
Emergency procedures	: Evacuate unnecessary personnel.
6.1.2. For emergency responders	
Protective equipment	: Equip cleanup crew with proper protection. Avoid breathing dust, fume, gas, mist, vapor spray.
Emergency procedures	: Ventilate area.
6.2. Environmental precautions	
Prevent entry to sewers and public waters.	Notify authorities if liquid enters sewers or public waters.
6.3. Methods and material for contain	inment and cleaning up
For containment	: Dam up the liquid spill.
Methods for cleaning up	: Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.
6.4. Reference to other sections	
See Heading 8. Exposure controls and pers	onal protection.
SECTION 7: Handling and storag	e
7.1. Precautions for safe handling	
Additional hazards when processed	: Handle empty containers with care because residual vapors are flammable. Hazardous waste
Precautions for safe handling	 Inditate cripty containers with cure bootdoor residual ruppers are naminaled. Indicated where due to potential risk of explosion. Pressurized container: Do not pierce or burn, even after use. No naked lights. No smoking. Use only non-sparking tools. Wash hands and other exposed
	areas with mild soap and water before eating, drinking tools. Wath hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. Do not spray on an ope flame or other ignition source. Obtain special instructions. Do not handle until all safety precautions have been read and understood. Avoid breathing dust,fume,gas,mist,vapor spray. Use only outdoors or in a well-ventilated area. Do not breathe dust,fumes,gas,mist,vapor spray
Hygiene measures	: Do not eat, drink or smoke when using this product. Wash affected areas thoroughly after handling.
7.2. Conditions for safe storage, inc	luding any incompatibilities
Technical measures	: Ground/bond container and receiving equipment. Use explosion-proof electrical, ventilating, lighting equipment . Proper grounding procedures to avoid static electricity should be followed.
Storage conditions	 Keep only in the original container in a cool, well ventilated place away from : Do not expose to temperatures exceeding 50 °C/ 122 °F. Keep in fireproof place. Keep container tightly closed.
Incompatible products	: Strong bases. Strong acids.
Incompatible materials	: Sources of ignition. Direct sunlight. Heat sources.
Storage area	: Store in a well-ventilated place.
-	
7.3. Specific end use(s)	
Follow Label Directions.	

Follow Label Directions.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Toluene (108-88-3)		
USA ACGIH	ACGIH TWA (mg/m ³)	37 mg/m³
USA ACGIH	ACGIH TWA (ppm)	10 ppm
USA ACGIH	ACGIH STEL (mg/m ³)	560
USA ACGIH	ACGIH STEL (ppm)	150 ppm
USA ACGIH	ACGIH Ceiling (ppm)	500 ppm
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm
USA OSHA	OSHA PEL (Ceiling) (ppm)	300 ppm
carbon dioxide, lique	fied, under pressure (124-38-9)	
USA ACGIH	ACGIH TWA (mg/m ³)	9000 mg/m ³
USA ACGIH	ACGIH TWA (ppm)	5000 ppm
USA ACGIH	ACGIH STEL (mg/m ³)	54000
USA ACGIH	ACGIH STEL (ppm)	30000 ppm
USA OSHA	OSHA PEL (TWA) (mg/m ³)	9000 mg/m ³
USA OSHA	OSHA PEL (TWA) (ppm)	5000 ppm
Methanol (67-56-1)		·
USA ACGIH	ACGIH TWA (mg/m³)	260 mg/m ³
USA ACGIH	ACGIH TWA (ppm)	200 ppm
USA ACGIH	ACGIH STEL (mg/m ³)	325 mg/m ³
USA ACGIH	ACGIH STEL (ppm)	250 ppm
USA ACGIH	ACGIH Ceiling (ppm)	1000 ppm
USA OSHA	OSHA PEL (TWA) (mg/m ³)	260 mg/m ³
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm
benzene (71-43-2)		
USA ACGIH	ACGIH TWA (ppm)	1 ppm
USA ACGIH	ACGIH STEL (ppm)	5 ppm
USA ACGIH	ACGIH Ceiling (ppm)	25 ppm
USA OSHA	OSHA PEL (TWA) (ppm)	1 ppm
USA OSHA	OSHA PEL (Ceiling) (ppm)	5 ppm
Acetone (67-64-1)		
USA ACGIH	ACGIH TWA (mg/m ³)	1200 mg/m ³
USA ACGIH	ACGIH TWA (ppm)	500 ppm
USA ACGIH	ACGIH STEL (mg/m ³)	1780 mg/m ³
USA ACGIH	ACGIH STEL (ppm)	750 ppm
USA ACGIH	ACGIH Ceiling (mg/m³)	0 mg/m ³
USA ACGIH	ACGIH Ceiling (ppm)	3000 ppm
USA OSHA	OSHA PEL (TWA) (mg/m ³)	2400 mg/m ³
USA OSHA	OSHA PEL (TWA) (ppm)	1000 ppm
acetone (67-64-1)		
USA ACGIH	ACGIH TWA (ppm)	500 ppm
USA ACGIH	ACGIH STEL (ppm)	500 ppm

8.2. Exposure controls

Appropriate engineering controls

: Local exhaust venilation, vent hoods.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Personal protective equipment

:	Gloves. Safety glasses. Avoid all unnecessary exposure.

Hand protection	: Wear protective gloves.
Eye protection	: Chemical goggles or safety glasses.
Skin and body protection	: Wear suitable protective clothing.
Respiratory protection	: Where exposure through inhalation may occur from use, respiratory protection equipment is recommended.
Other information	: Do not eat, drink or smoke during use.

Other information

SECTION 9: Physical and chemical	properties
9.1. Information on basic physical and	chemical properties
Physical state	: Gas
Appearance	: Colorless to pale yellow liquid.
Color	: Colorless.
Odor	: Characteristic.
Odor threshold	: No data available
рН	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: No data available
Freezing point	: < -78 °C (Lowest Component)
Boiling point	: 56.11 °C (Lowest Component)
Flash point	: -18 °C (Lowest Component)
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: 0.82
Density	: 0.82 g/cm ³
Solubility	: Poorly soluble in water.
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: Heating may cause a fire. Heating may cause an explosion.
Oxidizing properties	: No data available
Explosive limits	: No data available
9.2. Other information	
VOC content	: 45 %

: Liquefied gas Gas group

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. **Chemical stability**

Highly flammable liquid and vapor. May form flammable/explosive vapor-air mixture. Flammable aerosol. Contains gas under pressure; may explode if heated. Extreme risk of explosion by shock, friction, fire or other sources of ignition.

10.3.	Possibility of	hazardous	reactions

Not established.

10.4. **Conditions to avoid**

Direct sunlight. Extremely high or low temperatures. Heat. Sparks. Open flame. Overheating.

10.5. **Incompatible materials**

Strong acids. Strong bases.

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hazardous decomposition products May release flammable gases. Toxic fume Carl	
SECTION 11: Toxicological informati	
1.1. Information on toxicological effects	
Acute toxicity	: Toxic if swallowed. Toxic in contact with skin.
Toluene (108-88-3)	
LD50 oral rat	5580 mg/kg body weight
LD50 dermal rabbit	> 5000 mg/kg body weight LD50 quoted as 14.1 mL/kg (12267 mg/kg using density of 0.87)
LC50 inhalation rat (mg/l)	> 28.1 mg/l/4h (Rat; Air, Literature study)
Methanol (67-56-1)	
LD50 oral rat	>= 2528 mg/kg body weight application as 50% aqueous solution
LD50 dermal rabbit	17100 mg/kg corresponding to 20 ml/kg bw according to the authors
LC50 inhalation rat (mg/l)	128.2 mg/l/4h Air
benzene (71-43-2)	
LD50 oral rat	> 930 mg/kg (Rat; Equivalent or similar to OECD 401; Literature study; > 2000 mg/kg bodyweight; Rat; Experimental value)
LD50 dermal rabbit	> 8240 mg/kg (Rabbit; Experimental value; 21 CFR 191.10; > 9.4; Rabbit)
LC50 inhalation rat (mg/l)	43.767 mg/l/4h (Rat; Experimental value)
LC50 inhalation rat (ppm)	13700 ppm/4h (Rat; Experimental value)
Acetone (67-64-1)	
LD50 oral rat	5800 mg/kg (Rat; Equivalent or similar to OECD 401; Experimental value)
LD50 dermal rabbit	20000 mg/kg (Rabbit; Experimental value; Equivalent or similar to OECD 402)
LC50 inhalation rat (mg/l)	71 mg/l/4h (Rat; Experimental value; 76 mg/l/4h; Rat; Experimental value)
LC50 inhalation rat (ppm)	30000 ppm/4h (Rat; Experimental value)
acetone (67-64-1)	
LD50 oral rat	5800 mg/kg (Rat; Equivalent or similar to OECD 401; Experimental value)
LD50 dermal rabbit	20000 mg/kg (Rabbit; Experimental value; Equivalent or similar to OECD 402)
LC50 inhalation rat (mg/l)	71 mg/l/4h (Rat; Experimental value; 76 mg/l/4h; Rat; Experimental value)
LC50 inhalation rat (ppm)	30000 ppm/4h (Rat; Experimental value)
skin corrosion/irritation	: Causes skin irritation.
erious eye damage/irritation	: Not classified
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classifiedBased on available data, the classification criteria are not met
Carcinogenicity	: Not classified
Toluene (108-88-3)	
IARC group	3
benzene (71-43-2)	
IARC group	1
Reproductive toxicity	: Suspected of damaging fertility or the unborn child.Based on available data, the classification criteria are not met
pecific target organ toxicity (single exposure)	: Causes damage to organs. May cause drowsiness or dizziness.
pecific target organ toxicity (repeated xposure)	 May cause damage to organs through prolonged or repeated exposure.Based on available of the classification criteria are not met May cause damage to organs through prolonged or repeated exposure
spiration bazard	: Not classifiedBased on available data, the classification criteria are not met
Aspiration hazard Potential Adverse human health effects and symptoms	 Fatal if swallowed. Based on available data, the classification criteria are not met. Toxic if swallowed. Toxic in contact with skin.
Symptoms/injuries after inhalation	: Shortness of breath. May cause drowsiness or dizziness.
Symptoms/injuries after skin contact	 Shortness of breath may cause drowsness of dizzliness. Repeated exposure to this material can result in absorption through skin causing significant health hazard. Toxic in contact with skin. Causes skin irritation.
Symptoms/injuries after eye contact	: Causes serious eye damage.
Symptoms/injuries after ingestion	: Fatal if swallowed. Toxic if swallowed. Swallowing a small quantity of this material will result serious health hazard.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 12: Ecological information

12.1. Toxicity

Toluene (108-88-3)			
LC50 fish 1	24 mg/l 96 h; Salmo gairdneri (Oncorhynchus mykiss)		
EC50 Daphnia 1	84 mg/l (24 h; Daphnia magna; Locomotor effect)		
LC50 fish 2	13 mg/l (96 h; Lepomis macrochirus)		
EC50 Daphnia 2	11.5 - 19.6 mg/l (48 h; Daphnia magna)		
Threshold limit algae 1	> 400 mg/l (168 h; Scenedesmus quadricauda; Toxicity test)		
Threshold limit algae 2	105 mg/l (192 h; Microcystis aeruginosa)		
carbon dioxide, liquefied, under pressure (124-38-9)		
LC50 fish 1	35 mg/l (96 h; Salmo gairdneri (Oncorhynchus mykiss); Lethal)		
LC50 fish 2	60 - 240 mg/l (12 h; Salmo gairdneri (Oncorhynchus mykiss); Lethal)		
Mothenol (67 E6 1)			
Methanol (67-56-1)	15400 mg// (06 h; Lanomia magraphirus; Lathal)		
	15400 mg/l (96 h; Lepomis macrochirus; Lethal)		
EC50 Daphnia 1	> 10000 mg/l (48 h; Daphnia magna; Lethal)		
LC50 fish 2	10800 mg/l 96 h; Salmo gairdneri (Oncorhynchus mykiss)		
EC50 Daphnia 2	24500 mg/l (48 h; Daphnia magna)		
Threshold limit other aquatic organisms 1	6600 mg/l (16 h; Pseudomonas putida)		
Threshold limit algae 1	530 mg/l (192 h; Microcystis aeruginosa)		
Threshold limit algae 2	8000 mg/l (168 h; Scenedesmus quadricauda)		
benzene (71-43-2)			
LC50 fish 1	5.3 mg/l 96 h; Salmo gairdneri (Oncorhynchus mykiss)		
EC50 Daphnia 1	18 mg/l (24 h; Daphnia magna)		
EC50 other aquatic organisms 1	29 mg/l (72 h; Selenastrum capricornutum)		
LC50 fish 2	15.1 mg/l (96 h; Pimephales promelas)		
EC50 Daphnia 2	10 mg/l (48 h; Daphnia magna)		
TLM fish 1	22.5 mg/l (96 h; Lepomis macrochirus; Soft water)		
TLM fish 2	32 mg/l (96 h; Pimephales promelas; Hard water)		
TLM other aquatic organisms 1	10 - 100,96 h		
Threshold limit algae 2	50 mg/l (24 h; Phaeodactylum; Photosynthesis)		
Acetone (67-64-1)			
LC50 fish 1	6210 mg/l (96 h; Pimephales promelas; Nominal concentration)		
EC50 Daphnia 1 LC50 fish 2	8800 mg/l (48 h; Daphnia pulex) 5540 mg/l 96 h; Salmo gairdneri (Oncorhynchus mykiss)		
TLM fish 1	13000 ppm (96 h; Gambusia affinis; Turbulent water)		
TLM fish 2	> 1000 ppm (96 h; Pisces)		
Threshold limit other aquatic organisms 1	3000 mg/l (Plankton)		
Threshold limit other aquatic organisms 2	28 mg/l (Protozoa)		
Threshold limit algae 1	7500 mg/l (Scenedesmus quadricauda; pH = 7)		
Threshold limit algae 2	3400 mg/l (48 h; Chlorella sp.)		
acetone (67-64-1)			
LC50 fish 1	6210 mg/l (96 h; Pimephales promelas; Nominal concentration)		
EC50 Daphnia 1	8800 mg/l (48 h; Daphnia pulex)		
LC50 fish 2	5540 mg/l 96 h; Salmo gairdneri (Oncorhynchus mykiss)		
TLM fish 1	13000 ppm (96 h; Gambusia affinis; Turbulent water)		
TLM fish 2	> 1000 ppm (96 h; Pisces)		
Threshold limit other aquatic organisms 1	3000 mg/l (Plankton)		
Threshold limit other aquatic organisms 2	28 mg/l (Protozoa)		
Threshold limit algae 1	7500 mg/l (Scenedesmus quadricauda; pH = 7)		
Threshold limit algae 2	3400 mg/l (48 h; Chlorella sp.)		
12.2. Persistence and degradability			
	MASTER CARB & CHOKE CLEANER OTC COMPLIANT 16.25 OZ.		
Persistence and degradability	Not established.		
Toluene (108-88-3)			
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Low potential for adsorption in soil.		
Biochemical oxygen demand (BOD)	2.15 g O ₂ /g substance		

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Toluene (108-88-3)	
Chemical oxygen demand (COD)	2.52 g O ₂ /g substance
ThOD	3.13 g O ₂ /g substance
BOD (% of ThOD)	0.69 % ThOD
carbon dioxide, liquefied, under pressure (12	4-38-9)
Persistence and degradability	Biodegradability: not applicable. No (test)data on mobility of the substance available.
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable
Methanol (67-56-1)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil.
Biochemical oxygen demand (BOD)	$0.6 - 1.12 \text{ g } \text{O}_2 \text{ /g substance}$
Chemical oxygen demand (COD)	1.42 g O ₂ /g substance
ThOD	1.5 g O_2 /g substance
BOD (% of ThOD)	0.8 % ThOD
benzene (71-43-2)	
Persistence and degradability	Biodegradable in water. Ozonation in water. Forming sediments in water. Biodegradable in the soil. Photolysis in the air.
Biochemical oxygen demand (BOD)	2.18 g O ₂ /g substance
Chemical oxygen demand (COD)	2.15 g O ₂ /g substance
ThOD	3.10 g O ₂ /g substance
BOD (% of ThOD)	0.70 % ThOD
Acetone (67-64-1)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. No (test)data on mobility of the substance available. Not established.
Biochemical oxygen demand (BOD)	1.43 g O_2 /g substance
Chemical oxygen demand (COD)	1.92 g O_2 /g substance
ThOD	2.20 g O_2 /g substance
BOD (% of ThOD)	(20 day(s)) 0.872
acetone (67-64-1)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. No (test)data on mobility of the substance available.
Biochemical oxygen demand (BOD)	1.43 g O ₂ /g substance
Chemical oxygen demand (COD)	1.92 g O ₂ /g substance
ThOD	2.20 g O ₂ /g substance
BOD (% of ThOD)	(20 day(s)) 0.872
12.3. Bioaccumulative potential	
MASTER CARB & CHOKE CLEANER OTC CO	MPLIANT 16 25 07
Bioaccumulative potential	Not established.
· · ·	
Toluene (108-88-3)	
BCF fish 1	13.2 (Anguilla japonica)
BCF fish 2	90 (72 h; Leuciscus idus)
BCF other aquatic organisms 1	380 (24 h; Chlorella sp.; Fresh weight)
BCF other aquatic organisms 2	4.2 (Mytilus edulis; Fresh weight)
Log Pow	2.73 (Experimental value; Other; 20 °C)
Bioaccumulative potential Low potential for bioaccumulation (BCF < 500).	
carbon dioxide, liquefied, under pressure (12	
Log Pow Ricescumulative potential	0.83 (Experimental value)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
Methanol (67-56-1)	
BCF fish 1	< 10 (Leuciscus idus)
Log Pow	-0.77 (Experimental value; Other)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
benzene (71-43-2)	
BCF fish 1	19 Salmo gairdneri (Oncorhynchus mykiss)
L	
07/08/2014	EN (English LIS) 9/12

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

	, ,		
benzene (71-43-2)			
BCF other aquatic org	anisms 1	30 (24 h; Chlorella sp.; Fresh weight)	
Log Pow		2.13 (Experimental value)	
Bioaccumulative potential		Low potential for bioaccumulation (BCF < 500).	
Acetone (67-64-1)			
BCF fish 1		0.69 (Pisces)	
BCF other aquatic org	anisms 1	3	
Log Pow		-0.24 (Test data)	
Bioaccumulative poter	ntial	Not bioaccumulative. Not established.	
acetone (67-64-1)			
BCF fish 1		0.69 (Pisces)	
BCF other aquatic org	anisms 1	3	
Log Pow		-0.24 (Test data) Not bioaccumulative.	
Bioaccumulative poter		Not bloaccumulative.	
12.4. Mobility in so	bil		
Toluene (108-88-3)			
Surface tension		0.03 N/m (20 °C)	
Methanol (67-56-1)			
Surface tension		0.023 N/m (20 °C)	
benzene (71-43-2) Surface tension		0.029 N/m (20 °C)	
Acetone (67-64-1)			
Surface tension 0.0237 N/m		0.0237 N/m	
acetone (67-64-1)	acetone (67-64-1)		
Surface tension		0.0237 N/m	
12.5. Other advers	e effects		
Other information			
	osal consideration	S	
	ent methods		
Waste disposal recommendations		: Dispose in a safe manner in accordance with local/national regulations. Container under pressure. Do not drill or burn even after use. Dispose of contents/container to appropriate waste disposal facility, in accordance with local, regional, national, international regulations.	
Additional information		: Handle empty containers with care because residual vapors are flammable. Flammable vapors may accumulate in the container.	
Ecology - waste materials		: Avoid release to the environment. Hazardous waste due to toxicity.	
SECTION 14: Tran	sport information		
In accordance with ADR	R / RID / IMDG / IATA / AD	N	
US DOT (ground):	UN1950, Aerosols, 2.1,		
		-	
	ICAO/IATA (air): UN1950, Aerosols, 2.1, Limited Quantity		
IMO/IMDG (water):	UN1950, Aerosols, 2.1,	-	
Special Provisions:	N82 - See 173.306 of th	is subchapter for classification criteria for flammable aerosols.	
14.2. UN proper sh	nipping name		
DOT Proper Shipping Name		: Aerosols	
		flammable, (each not exceeding 1 L capacity)	
		: 2.1 - Class 2.1 - Flammable gas 49 CFR 173.115	
Classes Hazard labels (DOT)		: 2.1 - Flammable gas	
DOT Special Provisions (49 CFR 172.102)		: N82 - See 173.306 of this subchapter for classification criteria for flammable aerosols.	

EN (English US)

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Packaging Exceptions (49 CFR 173.xxx)	: 306
DOT Packaging Non Bulk (49 CFR 173.xxx)	: None
DOT Packaging Bulk (49 CFR 173.xxx)	: None
14.3. Additional information	
Emergency Response Guide (ERG) Number	: 24-HOUR EMERGENCY INFORMATION: CHEMTREC (800) 424-9300
Other information	: No supplementary information available.
Overland transport	
Class (ADR)	: 2 - Gases
Transport by sea	
DOT Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
DOT Vessel Stowage Other	: 48 - Stow "away from" sources of heat,87 - Stow "separated from" Class 1 (explosives) except Division 14,126 - Segregation same as for Class 9, miscellaneous hazardous materials
Air transport	
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 75 kg
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 150 kg

SECTION 15: Regulatory information		
15.1. US Federal regulations		
MASTER CARB & CHOKE CLEANER OTC C	OMPLIANT 16.25 OZ.	
SARA Section 311/312 Hazard Classes	Delayed (chronic) health hazard Fire hazard Immediate (acute) health hazard Sudden release of pressure hazard	
Toluene (108-88-3)		
Listed on United States SARA Section 313 Listed on the United States TSCA (Toxic Substa	ances Control Act) inventory	
SARA Section 311/312 Hazard Classes	Delayed (chronic) health hazard Fire hazard Immediate (acute) health hazard	
Methanol (67-56-1)		
Listed on United States SARA Section 313 Listed on the United States TSCA (Toxic Substances Control Act) inventory		
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Delayed (chronic) health hazard Fire hazard	
Acetone (67-64-1)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Fire hazard Delayed (chronic) health hazard	

15.2. International regulations

CANADA

MASTER CARB & CHOKE CLEANER OTC COMPLIANT 16.25 OZ.		
WHMIS Classification	Class B Division 5 - Flammable Aerosol Class D Division 2 Subdivision B - Toxic material causing other toxic effects	
Toluene (108-88-3)		
WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision A - Very toxic material causing other toxic effects	
Methanol (67-56-1)		
WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 1 Subdivision B - Toxic material causing immediate and serious toxic effects Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects	

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Acetone (67-64-1)	
Listed on the Canadian DSL (Domestic Sustances List)	
WHMIS Classification	Class B Division 2 - Flammable Liquid
	Class D Division 2 Subdivision B - Toxic material causing other toxic effects

EU-Regulations

Toluene (108-88-3)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Acetone (67-64-1)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)- Directive 79/831/EEC, sixth Amendment of Directive 67/548/EEC (dangerous substances) Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Classification according to Directive 67/548/EEC or 1999/45/EC

Repr.Cat.3; R63 F; R11 T; R39/23/24/25 Xn; R20/21/22 Xn; R48/20 Xi; R36/38 Full text of R-phrases: see section 16

15.2.2. National regulations

Acetone (67-64-1)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances) Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China) Listed on KECI (Korean Existing Chemicals Inventory) Listed on AICS (Australian Inventory of Chemical Substances) Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory Listed on the Korean ECL (Existing Chemicals List)

15.3. US State regulations

MASTER CARB & CHOKE CLEANER OTC COMPLIANT 16.25 OZ.()

State or local regulations U.S. - California - Proposition 65 - Maximum Allowable Dose Levels (MADL)

Acetone (67-64-1)				
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes				

Toluene (108-88-3)

U.S. - California - Proposition 65 - Maximum Allowable Dose Levels (MADL)

Acetone (67-64-1)

U.S. - California - Proposition 65 - Maximum Allowable Dose Levels (MADL)

Benzene 71-43-2

U.S. - Massachusetts - Right To Know List

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information : Revision - See : *. Indication of changes Other information : None. Full text of H-phrases: see section 16: Acute toxicity (dermal) Category 3

Acute toxicity (inhalation:dust,mist) Category 3

Acute Tox. 3 (Dermal) Acute Tox. 3 (Inhalation:dust,mist)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Acute Tox. 3 (Oral)Acute toxicity (oral) Category 3Asp. Tox. 1Aspiration hazard Category 1Compressed gasGases under pressure Compressed gasFlam. Aerosol 2Flammable aerosol Category 2Flam. Liq. 2Flammable liquids Category 2Repr. 2Reproductive toxicity Category 2Skin Irrit. 2Skin corrosion/irritation Category 2STOT RE 2Specific target organ toxicity (repeated exposure) Category 2STOT SE 1Specific target organ toxicity (single exposure) Category 1
Compressed gas Gases under pressure Compressed gas Flam. Aerosol 2 Flammable aerosol Category 2 Flam. Liq. 2 Flammable liquids Category 2 Repr. 2 Reproductive toxicity Category 2 Skin Irrit. 2 Skin corrosion/irritation Category 2 STOT RE 2 Specific target organ toxicity (repeated exposure) Category 2 STOT SE 1 Specific target organ toxicity (single exposure) Category 1
Flam. Aerosol 2 Flammable aerosol Category 2 Flam. Liq. 2 Flammable liquids Category 2 Repr. 2 Reproductive toxicity Category 2 Skin Irrit. 2 Skin corrosion/irritation Category 2 STOT RE 2 Specific target organ toxicity (repeated exposure) Category 2 STOT SE 1 Specific target organ toxicity (single exposure) Category 1
Flam. Liq. 2 Flammable liquids Category 2 Repr. 2 Reproductive toxicity Category 2 Skin Irrit. 2 Skin corrosion/irritation Category 2 STOT RE 2 Specific target organ toxicity (repeated exposure) Category 2 STOT SE 1 Specific target organ toxicity (single exposure) Category 1
Repr. 2 Reproductive toxicity Category 2 Skin Irrit. 2 Skin corrosion/irritation Category 2 STOT RE 2 Specific target organ toxicity (repeated exposure) Category 2 STOT SE 1 Specific target organ toxicity (single exposure) Category 1
Skin Irrit. 2 Skin corrosion/irritation Category 2 STOT RE 2 Specific target organ toxicity (repeated exposure) Category 2 STOT SE 1 Specific target organ toxicity (single exposure) Category 1
STOT RE 2 Specific target organ toxicity (repeated exposure) Category 2 STOT SE 1 Specific target organ toxicity (single exposure) Category 1
STOT SE 1 Specific target organ toxicity (single exposure) Category 1
STOT SE 3 Specific target organ toxicity (single exposure) Category 3
H223 Flammable aerosol
H225 Highly flammable liquid and vapor
H280 Contains gas under pressure; may explode if heated
H301 Toxic if swallowed
H304 May be fatal if swallowed and enters airways
H311 Toxic in contact with skin
H315 Causes skin irritation
H331 Toxic if inhaled
H336 May cause drowsiness or dizziness
H361 Suspected of damaging fertility or the unborn child
H370 Causes damage to organs
H373 May cause damage to organs through prolonged or repeated
exposure

NFPA health hazard	: 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.
NFPA fire hazard	: 3 - Liquids and solids that can be ignited under almost all ambient conditions.
NFPA reactivity	: 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.
HMIS III Rating	
Health	: 2 Moderate Hazard - Temporary or minor injury may occur
Flammability	: 3 Serious Hazard
Physical	: 1 Slight Hazard
Personal Protection	: B

SDS US (GHS HazCom 2012)

The Supplier identified in Section 1 of this MSDS has evaluated this product and certifies it to be labeled and packaged in compliance with the applicable provisions of the Federal Hazardous Substance Act as stated in 16 CFR 1500 and enforced by the Consumer Product Safety Commission, and where applicable the products that require Child Resistant Closures are packaged in accordance with the Poison Prevention Packaging Act as stated in 16 CFR 1700 and enforced by the Consumer Product Safety Commission. All closures have been tested in accordance with the latest protocols. No other testing is required to certify compliance with the above. The date of manufacture is stamped on the product

Disclaimer: The information and recommendations contained herein are based upon tests believed to be reliable. However, the manufacturer/distributor of this product does not guarantee their accuracy or completeness NOR SHALL ANY OF THIS INFORMATION CONSTITUTE A WARRANTY, WHETHER EXPRESSED OR IMPLIED, AS TO THE SAFETY OF THE GOODS, THE MERCHANTABILITY OF THE GOODS, OR THE TITNESS OF THE GOODS FOR A PARTICULAR PURPOSE. Adjustment to conform to actual conditions of usage may be required. The manufacturer/distributor assumes no responsibility for results obtained or for incidental or consequential damages, including lost profits, arising from the use of these data. No warranty against infringement of any patent, copyright or trademark is made or implied.