Printing date 01/25/2016 Revised On 01/25/2016

#### 1 Identification of the substance and manufacturer

Trade name: **FLUORESCENT ORANGE** 

0000200357 Product code:

**Product category** PC9a Paints and coatings. Seymour of Sycamore Manufacturer/Supplier:

917 Crosby Avenue Sycamore, IL 60178 Phone: 815-895-9101 www.seymourpaint.com

**Emergency telephone number:** CHEMTEL 1-800-255-3924, or 813-248-0585.

#### 2 Hazard(s) identification

#### Classification of the substance or mixture

Flam. Aerosol 1 H222 Extremely flammable aerosol.

Press. Gas H280 Contains gas under pressure; may explode if heated.

STOT SE 3 H335 May cause respiratory irritation.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

**GHS Hazard pictograms** 

**Precautionary statements** 

GHS02 GHS04 GHS07 GHS08

Signal word Danger

Hazard statements Extremely flammable aerosol.

Contains gas under pressure; may explode if heated.

May cause respiratory irritation.

May cause damage to organs through prolonged or repeated exposure. Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Do not spray on an open flame or other ignition source.

Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area.

Do not breathe dust/fume/gas/mist/vapors/spray.

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.

Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Protect from sunlight. Store in a well-ventilated place. Store in a well-ventilated place. Keep container tightly closed.

Dispose of contents/container in accordance with local/regional/national/international

regulations.

## 3 Composition/information on ingredients

**Chemical characterization: Mixtures** 

Chemical Description: This product is a mixture of the substances listed below with nonhazardous additions

Chemical Becomplion.	This product is a mixture of the substances holes below with horniazarasas additions.	
Dangerous components:		
74-98-6 propane		13.87%
64742-89-8 VM&P Naphtha		11.08%
1317-65-3 Calcium Carbonate		10.4%
1330-20-7 xylene (mix)		8.99%
106-97-8 n-butane		8.15%
64742-47-8 Mineral Spirits		3.36%
100-41-4 ethyl benzene		1.62%

#### 4 First-aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints.

Remove contaminated clothing. Wash exposed area with soap and water. After skin contact: Rinse opened eye for several minutes under running water. Then consult a doctor. After eye contact:

After swallowing: Rinse out mouth and then drink plenty of water. Rinse mouth with water. Do not induce vomiting.

Most important symptoms and effects:

Indication of any immediate medical

attention needed: No further relevant information available.

#### 5 Fire-fighting measures

**Extinguishing agents:** 

CO2, extinguishing powder or water spray. Fight larger fires with water spray.

Special hazards: Can form explosive gas-air mixtures.

Protective equipment for firefighters: A respiratory protective device may be necessary.

## 6 Accidental release measures

Personal precautions, protective equipment and emergency

procedures:

Wear protective equipment. Keep unprotected persons away.

Use respiratory protective device against the effects of fumes/dust/aerosol.

(Contd. on page 2)

(Contd. of page 1)

Printing date 01/25/2016 Revised On 01/25/2016

Trade name: FLUORESCENT ORANGE

Methods and material for

Ensure adequate ventilation.

7 Handling and storage

Precautions for safe handling

containment and cleaning up:

Use only in well ventilated areas.

Storage requirements:

Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions. Store locked up.

# 8 Exposure controls/personal protection

	4-96-6 propane	
PEL (USA)	Long-term value: 1800 mg/m³, 1000 ppm	
REL (USA)	Long-term value: 1800 mg/m³, 1000 ppm	
TLV (USA)	refer to Appendix F inTLVs and BFIs book	

Components with limit values that require monitoring at the workplace:

1330-20-7 xylene (mix)

PEL (USA) Long-term value: 435 mg/m³, 100 ppm REL (USA) Short-term value: 655 mg/m³, 150 ppm Long-term value: 435 mg/m³, 100 ppm Short-term value: 651 mg/m³, 150 ppm Long-term value: 434 mg/m³, 100 ppm TLV (USA)

106-97-8 n-butane

REL (USA) Long-term value: 1900 mg/m³, 800 ppm TLV (USA) Short-term value: 2370 mg/m³, 1000 ppm

100-41-4 ethyl benzene

Long-term value: 20 ppm IARC 2B EL (USA)

PEL (USA) Long-term value: 435 mg/m³, 100 ppm REL (USA) Short-term value: 545 mg/m³, 125 ppm Long-term value: 435 mg/m³, 100 ppm TLV (USA) Long-term value: 87 mg/m³, 20 ppm

Ingredients with biological limit values:

## 1330-20-7 xylene (mix)

BEI (USA) 1.5 g/g creatinine

Medium: urine Time: end of shift

Parameter: Methylhippuric acids

# 100-41-4 ethyl benzene

BEI (USA) 0.7 g/g creatinine

Medium: urine

Time: end of shift at end of workweek

Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)

Medium: end-exhaled air Time: not critical

Parameter: Ethyl benzene (semi-quantitative)

Keep away from foodstuffs and animal feed. Wash hands after use. Hygienic protection:

Wash hands after use.

Do not eat or drink while working.

**Breathing equipment:** A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a charcoal filter respirator should be

worn. If you suspect overexposure conditions exist, please consult an authority on chemical

hygeine.

Hand protection: Nitrile gloves.

Protective gloves. The glove material must be impermeable and resistant to the substance.

Eye protection: Tightly sealed goggles

## 9 Physical and chemical properties

Appearance: Aerosol. Odor: Aromatic **Odor threshold:** Not determined. pH-value: Melting point/Melting range Not determined. Undetermined. **Boiling point:** -44 °C (-47 °F) -19 °C (-2 °F) Flash point:

Flammability (solid, gas): Extremely flammable. **Decomposition temperature:** Not determined.

Auto igniting: Product is not self-igniting.

Danger of explosion: In use, may form flammable/explosive vapour-air mixture.

**Lower Explosion Limit:** 1.7 Vol %

(Contd. on page 3)

(Contd. of page 2)

Printing date 01/25/2016 Revised On 01/25/2016

Trade name: FLUORESCENT ORANGE

**Upper Explosion Limit:** 10.9 Vol %

Vapor pressure: Not determined.

Between 0.77 and 0.85 (Water equals 1.00) **Relative Density:** 

Vapour density Not determined. **Evaporation rate** Not applicable. Partition coefficient: n-octonal/water: Not determined. Solubility: Not determined. Viscosity: Not determined. **VOC** content: 506.6 g/l / 4.23 lb/gl

**VOC content (less exempt solvents):** 47.4 % 31.3 % Water: MIR Value: 1.08

20.2 % Solids content:

10 Stability and reactivity

Reactivity: Stable at normal temperatures.

Conditions to avoid: Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing

temperatures.

Chemical stability: Not fully evaluated.

Possibility of hazardous reactions: No dangerous reactions known. Incompatible materials: No further relevant information available. Hazardous decomposition: No dangerous decomposition products known.

#### 11 Toxicological information

LD/LC50 values that are relevant for classification:			
1330-20-7 xylene (mix)			
Oral	LD50	8700 mg/kg (rat)	
Dermal	LD50	2000 mg/kg (rht)	

2000 mg/kg (rbt) Inhalative LC50/4 h 6350 mg/l (rat)

106-97-8 n-butane

Oral

Inhalative LC50/4 h 658 mg/l (rat)

100-41-4 ethyl benzene 3500 mg/kg (rat) LD50

Dermal LD50 17800 mg/kg (rbt) Information on toxicological effects: No data available. Skin effects: No irritant effect.

Eve effects: No irritating effect.

Sénsitization: No sensitizing effects known.

Carcinogenic categories

IARC (International Agen	cy for Research on Cancer)
--------------------------	----------------------------

1330-20-7 xylene (mix) 100-41-4 ethyl benzene

NTP (National Toxicology Program)

None of the ingredients is listed.

## 12 Ecological information

Aquatic toxicity:
Persistence and degradability: Hazardous for water, do not empty into drains.

The product is degradable after prolonged exposure to natural weathering processes.

Bioaccumulative potential: No further relevant information available. Mobility in soil: No further relevant information available. Other adverse effects: No further relevant information available.

## 13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

Recommendation: Completely empty cans should be recycled.

#### 14 Transport information

**UN-Number** UN1950 DOT N/A UN1950

DOT Consumer Commodity ORM-D

Aerosols, flammable

1950 Aerosols

Transport hazard class(es):

Class Marine pollutant:

Special precautions for user: Warning: Gases

**EMS Number:** F-D,S-Ŭ

(Contd. on page 4)

3 2B

D

Printing date 01/25/2016 Revised On 01/25/2016

Trade name: FLUORESCENT ORANGE

(Contd. of page 3)

**ADR** 

**Excepted quantities (EQ)** Code: E0

Not permitted as Excepted Quantity

**IMDG** 

Limited quantities (LQ) Excepted quantities (EQ)

1L Code: E0

Not permitted as Excepted Quantity

Packaging Group: UN "Model Regulation": UN1950, Aerosols, 2.1

15 Regulatory information

SARA Section 355 (extremely hazardous substances):

None of the ingredients in this product are listed.

SARA Section 313 (Specific toxic chemical listings):

1330-20-7 xylene (mix)

100-41-4 ethyl benzene

CPSC: This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

California Proposition 65 chemicals known to cause cancer:

100-41-4 ethyl benzene

CANADIAN ÉNVIRONMENTAL

**PROTECTION ACT:** 

WHMIS Symbols for Canada:

All hazardous ingredients for this product appear on the Canadian Domestice Substance List.

A - Compressed gas



EPA:

1330-20-7 xylene (mix)

100-41-4 ethyl benzene

16 Other information

Contact: Date of preparation / last revision

Regulatory Affairs 01/25/2016 / -